

# Casing

Products Range	4-1/2" ~ 20" (φ 114.3 ~ φ 508mm)
Grade	H40, J55, K55, L80, C95, N80, C90, T95, P110
Type of End Finish	STC, LTC, BTC



## Available Sizes and Grades

Outside Diameter	Nominal Weight	Outside Diameter D	Wall Thickness t		Type of End Finish					
					Grade					
					H-40	J-55 K-55	L-80 C-95	N-80	C-90 T-95	P-110
in	lb/ft	mm	in	mm						
4-1/2	9.50	114.3	0.205	5.21	S	S	-	-	-	-
	10.50	114.3	0.224	5.69	-	SB	-	-	-	-
	11.60	114.3	0.250	6.35	-	SLB	LB	LB	LB	LB
	13.50	114.3	0.290	7.37	-	-	LB	LB	LB	LB
5	11.50	127.0	0.220	5.59	-	S	-	-	-	-
	13.00	127.0	0.253	6.43	-	SLB	-	-	-	-
	15.00	127.0	0.296	7.52	-	SLB	LB	LB	LB	LB
	18.00	127.0	0.362	9.19	-	-	LB	LB	LB	LB
	21.40	127.0	0.437	11.10	-	-	LB	LB	LB	LB
	23.20	127.0	0.478	12.14	-	-	LB	LB	LB	LB
	24.10	127.0	0.500	12.70	-	-	LB	LB	LB	LB
5-1/2	14.00	139.7	0.244	6.20	S	S	-	-	-	-
	15.50	139.7	0.275	6.99	-	SLB	-	-	-	-
	17.00	139.7	0.304	7.72	-	SLB	LB	LB	LB	LB
	20.00	139.7	0.361	9.17	-	-	LB	LB	LB	LB
	23.00	139.7	0.415	10.54	-	-	LB	LB	LB	LB
6-5/8	20.00	168.3	0.288	7.32	S	SLB	-	-	-	-
	24.00	168.3	0.352	8.94	-	SLB	LB	LB	LB	LB
	28.00	168.3	0.417	10.59	-	-	LB	LB	LB	LB
	32.00	168.3	0.475	12.07	-	-	LB	LB	LB	LB
7	17.00	177.8	0.231	5.87	S	-	-	-	-	-
	20.00	177.8	0.272	6.91	S	S	-	-	-	-
	23.00	177.8	0.317	8.05	-	SLB	LB	LB	LB	-
	26.00	177.8	0.362	9.19	-	SLB	LB	LB	LB	LB
	29.00	177.8	0.408	10.36	-	-	LB	LB	LB	LB
	32.00	177.8	0.453	11.51	-	-	LB	LB	LB	LB
	35.00	177.8	0.498	12.65	-	-	LB	LB	LB	LB
	38.00	177.8	0.540	13.72	-	-	LB	LB	LB	LB
	7-5/8	24.00	193.7	0.300	7.62	S	-	-	-	-
26.40		193.7	0.328	8.33	-	SLB	LB	LB	LB	-
29.70		193.7	0.375	9.53	-	-	LB	LB	LB	LB
33.70		193.7	0.430	10.92	-	-	LB	LB	LB	LB
39.00		193.7	0.500	12.70	-	-	LB	LB	LB	LB
42.80		193.7	0.562	14.27	-	-	LB	LB	LB	LB
45.30		193.7	0.595	15.11	-	-	LB	LB	LB	LB
47.10		193.7	0.625	15.88	-	-	LB	LB	LB	LB
8-5/8		24.00	219.1	0.264	6.71	-	S	-	-	-
	28.00	219.1	0.304	7.72	S	-	-	-	-	-
	32.00	219.1	0.352	8.94	S	SLB	-	-	-	-
	36.00	219.1	0.400	10.16	-	SLB	LB	LB	LB	-
	40.00	219.1	0.450	11.43	-	-	LB	LB	LB	LB
	44.00	219.1	0.500	12.70	-	-	LB	LB	LB	LB
	49.00	219.1	0.557	14.15	-	-	LB	LB	LB	LB

Outside Diameter	Nominal Weight	Outside Diameter D	Wall Thickness t		Type of End Finish					
					Grade					
					H-40	J-55 K-55	L-80 C-95	N-80	C-90 T-95	P-110
in	lb/ft	mm	in	mm						
9-5/8	32.30	244.5	0.312	7.92	S	-	-	-	-	-
	36.00	244.5	0.352	8.94	S	SLB	-	-	-	-
	40.00	244.5	0.395	10.03	-	SLB	LB	LB	LB	-
	43.50	244.5	0.435	11.05	-	-	LB	LB	LB	LB
	47.00	244.5	0.472	11.99	-	-	LB	LB	LB	LB
	53.50	244.5	0.545	13.84	-	-	LB	LB	LB	LB
10-3/4	58.40	244.5	0.595	15.11	-	-	LB	LB	LB	LB
	32.75	273.1	0.279	7.09	S	-	-	-	-	-
	40.50	273.1	0.350	8.89	S	SB	-	-	-	-
	45.50	273.1	0.400	10.16	-	SB	-	-	-	-
	51.00	273.1	0.450	11.43	-	SB	SB	SB	SB	SB
	55.50	273.1	0.495	12.57	-	-	SB	SB	SB	SB
	60.70	273.1	0.545	13.84	-	-	-	-	SB	SB
11-3/4	65.70	273.1	0.595	15.11	-	-	-	-	SB	SB
	42.00	298.5	0.333	8.46	S	-	-	-	-	-
	47.00	298.5	0.375	9.53	-	SB	-	-	-	-
	54.00	298.5	0.435	11.05	-	SB	-	-	-	-
13-3/8	60.00	298.5	0.489	12.42	-	SB	SB	SB	SB	SB
	48.00	339.7	0.330	8.38	S	-	-	-	-	-
	54.50	339.7	0.380	9.65	-	SB	-	-	-	-
	61.00	339.7	0.430	10.92	-	SB	-	-	-	-
	68.00	339.7	0.480	12.19	-	SB	SB	SB	SB	SB
16	72.00	339.7	0.514	13.06	-	-	SB	SB	SB	SB
	65.00	406.4	0.375	9.53	S	-	-	-	-	-
	75.00	406.4	0.438	11.13	-	SB	-	-	-	-
18-5/8	84.00	406.4	0.495	12.57	-	SB	-	-	-	-
	87.50	473.1	0.435	11.05	S	SB	-	-	-	-
20	94.00	508.0	0.438	11.13	SL	SLB	-	-	-	-
	106.50	508.0	0.500	12.70	-	SLB	-	-	-	-
	133.00	508.0	0.635	16.13	-	SLB	-	-	-	-

S = Short Round Thread      L = Long Round Thread      B = Buttress Thread